










MONOCRYSTALLINE SINGLE GLASS 435-460W REESUN120H-182M

High efficiency and low LID
PERC monocrystalline technology
HALF-CELL technology

-  Excellent Anti-PID performance
-  Guaranteed power tolerance (0 ~+5W)
-  Excellent wind and snow loads up to 5400Pa under specific installation methods
-  Lower current, higher power generation, lower risk of hot spots
-  Excellent low irradiation performance
-  Higher component conversion efficiency (up to 21.26%)
-  12-year product quality warranty, 25-year linear output power warranty



Comprehensive Product And System Certification

IEC 61215, IEC 61730

ISO 9001:2015: ISO Quality Management System Certification

ISO 14001:2015: ISO Environmental management system certification

ISO 45001:2018 Occupational Health and Safety Management System Certification



*Reesun Solar reserves the right to interpret technical changes and test specifications.

REESUN120H-182M 435-460W

Electrical Performance Parameters


Maximum power test tolerance : $\pm 3\%$

Component model	435W		440W		445W		450W		455W		460W	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Testing environment	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum power [Pmax/W]	435	326	440	329	445	332	450	335	455	338	460	341
Maximum power voltage [Vmp/V]	33.84	31.48	33.95	31.60	34.07	31.71	34.18	31.83	34.30	31.95	34.41	32.05
Maximum power current [Imp/A]	12.93	10.34	13.01	10.40	13.09	10.46	13.17	10.52	13.25	10.58	13.33	10.64
Open circuit voltage [Voc/V]	40.94	38.64	41.05	38.75	41.17	38.86	41.28	38.96	41.40	39.06	41.51	39.16
Short circuit current [Isc/A]	13.61	10.99	13.69	11.06	13.77	11.12	13.85	11.19	13.93	11.25	14.01	11.32
Component efficiency [%]	20.10		20.34		20.57		20.80		21.03		21.26	

Maximum power test Common Standard Test Environment (STC) irradiance 1000W/m², atmospheric quality AM1.5, module temperature 25 ° C
Nominal operating battery temperature (NOCT): irradiance 800W/m², ambient temperature 20 ° C, atmospheric quality AM1.5, wind speed 1m/s

Mechanical And Operating Parameters

Number of battery cells	120(6×20)
Junction box	IP68 Three diodes
Output cable	4mm ² , length 300mm, Customizable length
Glass	3.2mm Single layer coated tempered glass
Frame	Anodized aluminum alloy frame
Weight	24kg \pm 3%
Size	1908×1134×35mm
Packing	31pcs per pallet 744pcs per 40'HC
Working temperature	-40°C ~ +85°C
Power tolerance	0~+5 W
Current and voltage tolerance	$\pm 4\%/\pm 3\%$
Maximum system voltage	DC1500V (IEC)
Maximum fuse current rating	25A
Nominal operating battery temperature	45 \pm 2°C
Safety level	Class II
Fire rating	Class C



Temperature Coefficient(STC)

Short circuit current temperature coefficient of frame section	+0.048%/°C
Open circuit voltage temperature coefficient	-0.270%/°C
Maximum power temperature coefficient	-0.350%/°C

Mechanical Load

Front maximum static load	5400Pa
Maximum back static load	2400Pa
Hail test	25mm hail, impact at 23 m/s

I-V Curve (REESUN120H-182M-450W)

